Technical Datasheet

NITRO SOLVENT



In case of interior use of NITRO SOLVENT take

care of good ventilation, avoid any source of

ignition and breathing vapors of solvent and take

fire extinguishing measures. Do not smoke. Take

safety measures written in containers label. For

more information you can consult the material

safety data sheet edited by the company. Lower

consumption of solvent is efficient after evaluating

necessary quantity for use. Recover and use again

quantity of solvent retaining it to tight sealed container. Do not let liquid material in ground or

draining water. Disposal of material need to be

done according information from local disposal

NITRO SOLVENT is delivered in 0.75lt, 4lt, 20lt

Product has a shelf-life of 36 months in tight

sealed containers and should be stored between

3-30°C. Protect the product packaging from direct

Notifications on use

authorities.

Packaging

containers.

Shelf-Life - Storage

sun light and frost.

Page 1 out of 1

Product Information

NITRO SOLVENT is a specially designed solvent mixture of aromatic hydrocarbons and special esters & ketones that is intended to be used in dilution of EXTRA VERNICHROM, DUCO PLUS, ARMOR ANTI-RUST, CHASSICOT, PRIMER SOLVENT in application of airless spray. It offers fast evaporation, better dilution and workability, fast drying promoting easy application and film leveling according to proper application.

It can be also used as a cleaning tools media or surface cleaner before application against dust, rust, lubricating oils or petroleum substances.

Product Properties

Color:	Transparent
Density:	0.85 ± 0.02 g/ml
(EN ISO 2811-1)	

Product Information

Before use of NITRO SOLVENT be informed on the recommended percentage of mixing with the respective product, so as to have optimum results. After mixing make an easy agitation until homogeneity is achieved. Consumption is depended on the proposed maximum percentage to be used and the surface condition.

TO XROMA

CERTIFIED MS ISO 9001 ISO 14001 ISO 45001

21st KM O.N.R.Thessaloniki - Kavala -P.C. 57200/Tel. 2394052451/Info: www.toxroma.gr

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product. | Edition: 20.04.2023