

PRIMER SOLVENT

Product Information

PRIMER SOLVENT is an acrylic, solvent based, binding primer for exterior use. It promotes adhesion and enhance workability of the substrate for further application. It can be used over new or old surfaces as a substrate for all kind of coatings for exterior use like paints, render-plaster, or elastomeric products.

Drying and recoat time is short. Thanks to its penetration it enters the walls' pores preventing moisture from passing inside the building while allowing the buildings structure to breathe.

Product Properties

<i>Color:</i>	Transparent – Light Yellowish
<i>Density:</i>	0.87 g/ml (23°C)
<i>Time to touch:</i>	1 hour (23°C)
<i>Time to recoat:</i>	2 hours (23°C)

Substrate Preparation-Product Application

Substrate should be clean and free from loose particles, dust, oily or greasy materials.

Before use mix well, dilute till 100% with WHITE SPIRIT, homogenize and apply the product in one coat.

TO XROMA

21st KM O.N.R.Thessaloniki - Kavala -P.C. 57200/Tel. 2394052451/Info: www.toxroma.gr

This results in a total consumption of product itself of 14-16 m²/lt depending on the absorption of the substrate.

Roller, brushes or airless systems can be used for application and should be cleaned thoroughly immediately after use with WHITE SPIRIT or NITRO SOLVENT.

Conditions during application should be 10-35°C and humidity not exceeding 80%.

Packaging

The product is delivered in 1lt, 5lt, 20lt containers.

Shelf Life - Storage

Product has a 24 months shelf life in tight closed package that should be stored in 5-35 °C and protected from direct sun light and frost.

Volatile Organic Compounds (VOC)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type S, is 750 g/lt (2010) for the ready-to-use product.

The ready-to-use product PRIMER SOLVENT contains a maximum of VOC<750 g/lt.



The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore, the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product .01/03-03-2023